

# IMPI 520T VA

## Design Sound Projector 20 W

### FEATURES

EN 54 24

- The 20W design speaker with an amazing concave shape is equipped with a 130mm full-range speaker and a 100V transformer with 3 power adjustments 20/10/5W.
- Acoustically the design loudspeaker convinces at all levels. Thanks to a smart phase-shifting and a high-quality midrange resonator, the speaker offers a sound characteristic that is matching a 2-way system.
- In addition, the very wide dispersion ensures a comprehensive sound.
- A robust, ABS plastic housing in RAL9016 and a stable aluminium mounting bracket guarantee a durable installation.
- The cable is fed via a cable gland (PG11). The integrated 2x2-pole ceramic block and thermal fuse as well as the moisture impregnation of the loudspeaker ensure additional safety.



### TECHNICAL CHARACTERISTICS

MODEL		IMPI 520T VA							
Power	Dimensions (LxWxH)	Weight	Color	Sensitivity (1W/4W) EN 54-24	Frequency response (Hz)	Directivity 500 Hz	Directivity 1 kHz	Directivity 2 kHz	Directivity 4 kHz
20 / 10 / 5W	169 x 283,5 mm	1,76 kg	White	76,4 dB	142 > 14,3 K	H : 360° V : 360°	H : 155° V : 220°	H : 95° V : 85°	H : 85° V : 84°

### MOUNTING INSTRUCTIONS

1. Put the mounting bracket onto the wall.
2. Fix the bracket with the adapted screws, without dismantling the projector.
3. Remove the back cover and put the incoming cable thru the cable entry.
4. Connect cable to the ceramic terminal.
5. Replace the back cover and push it in as far as possible. The hood is held in place by tightening.
6. Screw the speaker to the bracket.

Power Tappings	
Black	COM
Brown	20 W
Red	10 W
Yellow	5 W

 n° 1438 22 Certificate n° : 1438-CPR-0869	EN 54-24 Speaker for voice alarm systems for systems for fire detection systems and fire alarm systems in buildings
	IMPI 520T VA Type B